



Refrigeration

NEO CONCEPT+ Refrigerated cabinets

NEO CONCEPT+ REFRIGERATED CABINET, CPAFP-801

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	653,00	750,00
Depth	mm	796,00	850,00
Height	mm	1.996,00	2.150,00
Weight	Kg	120,00	130,00
Volume	m3	1,04	1,37

<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	0,42
Voltage 230V -1+N			2x1,5+T - 4 A
Voltage 230V - III			
Voltage 400V - III+N			

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION 250 g. // R-404 A

Certification EQNET- CE SGS-2103-0906-1

NEO CONCEPT+ REFRIGERATED CABINET, CPAFP-801
 Refrigerated cabinet for GN-1/1 size grids.
 External case made in stainless steel, except rear panel.
 Interior in stainless steel
 Recessed interior with curved angles for easy cleaning.
 Interior with stamped racks.
 Drainage on the floor.
 Reversible doors, with automatic closing device and open fastening at 90 °.
 Monoblock structure with 60-mm injected polyurethane insulation, injected at high pressure with density of 40 kg/m3, CFC-free.
 Compact cold system, highly effective and efficient, located outside the chamber in monoblock system.
 Ecological coolant R-404 A, CFC-free.
 Pivoting grid door for maintenance.
 Airtight compressor with ventilated condenser
 Evaporator installed outside the chamber, for increased storage capacity.
 Forced draft refrigeration with optimised air circulation.
 Automatic evaporation of water from defrosting by hot gas.
 Alarm to prevent prolonged opening of the door.
 ECO function allows for more efficient and affordable operation , with energy savings of up to 12% compared to standard equipment. Ideal for periods when the doors are rarely opened (for example, at night).
 Electronic and digital temperature and defrost control.
 Internal light. LED lighting.
 Adjustable stainless steel legs.
 Epoxy shelves that can be regulated in height.
 3 racks per section.
 Working temperature: -2 °C, +8 °C at room temperature of 38°C.
 Climate classification 5.
 Thermostat temperature control with indicator.
 Operating voltage 220/240 V - 1+N.
 Equipment: 3 shelves by module.
 N. of doors: 1 big door.
 Capacity (litres): 600.
 Refrigeration power: 275 W.
 Total electric power: 411 W.
 Dimensions: 653 x 796 x 1996 mm.

Connections	X	Y	Z	Diameter	Information
ELECTRICITY	200	5	1.840		Prever Interruptor diferencial

