



**Catalogue**  
**CATERING**  
**Chapter**  
**REFRIGERATION**

**Model**  
**EMAFP-801 230V 1N 50Hz**

19037603

04/04/2019

**REFRIGERATED CABINET MONOBLOCK, EMAFP-801**


- Constructed in AISI-304 stainless steel.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- Inner LED lights with power switch.
- 60 mm, 40 kg/m3 injected polyurethane insulation.
- Embedded inner tray slides. Storage trays at 23 different levels 55 mm from each other.
- Forced draught system with cooling unit outside the room and monoblock system to optimise storage capacity.
- Removable plastic covered steel grid shelves (GN 2/1) for easy cleaning. Equipment: 3 shelves per large door.
- Working temperature: from -2 °C to +8 °C. Ambient temperature: 43 °C (Except specific intensive usage).
- Number of doors: 1

**Options:**

- Locks.
- Castor kit (factory assembly).
- Reversible door.
- Tropicalised unit.
- HACCP.
- Door opening pedal (factory assembly).
- "- Stainless steel back panel.
- "

**DIMENSIONS**

X Width	653 mm	X Gross width	730 mm
Y Depth	796 mm	Y Gross depth	860 mm
Z Height	1996 mm	Z Gross height	2017 mm
Net Weight	144,0 kg	Gross Weight	151,0 kg
Net volume	1,037 m3	Gross volume	1,266 m3



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,128 kW
Voltage	230V - 1N
Amperage	0,6 A
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,219 kW
Annual elec. consumption	423,00 kWh
Power consumption 24h	1,16 kWh
Gross internal volume	572 L
Refrigeration net.vol	432 L
Climate class	4
Cooling gas load	95,000 g
Clasif. Energy efficiency	B

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------



Catalogue  
**CATERING**

Chapter  
**REFRIGERATION**

Model  
**EMAFP-801 230V 1N 50Hz**

19037603

04/04/2019

