



Catalogue
CATERING
Chapter
REFRIGERATION

Model

19047063

01/03/2019


WINE DISPLAY CABINETS, WR-180

SPECIFICATIONS

Pre-lacquered steel outside. Sanitary thermoformed plastic inside with embedded inner tray slides (polystyrene).
 45 mm, 40 kg/m³ injected polyurethane isolation.
 Forced draught cooling system with low vibration compressor.
 Inner evaporator with forced draught. Outer low maintenance condenser with forced draught.
 Digital display for electronic and digital control of temperature and defrosting.
 Double pane door with tinted glass and UV filter for sunlight protection.
 Black plastic covered steel grid removable shelves for easy cleaning.
 Equipment: 3 flat shelves and 1 tipped shelf for main bottles or the conservation of opened bottles (models WR-300/600) one flat unit for model WR-180.
 LED vertical lighting system.
 Working temperature: +5 °C, +16 °C (Room temperature: 32 °C).

Doors: 1
 Capacity: 130 L
 Bottle capacity: 25

DIMENSIONS



X Width	505 mm	X Gross width	520 mm
Y Depth	570 mm	Y Gross depth	595 mm
Z Height	950 mm	Z Gross height	1095 mm
Net Weight	44,0 kg	Gross Weight	49,7 kg
Net volume	0,273 m ³	Gross volume	0,339 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,227 kW
Voltage	230V - 1N
Amperage	1,7A
Electric frequency	50/60Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-134a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,178 kW
Climate class	4
Cooling gas load	210,000 g

UNDERTAKEN TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	1+N
--------------------------	-----

