



Catalogue
CATERING
Chapter
REFRIGERATION

Model

19046032

01/03/2019

WINE DISPLAY CABINETS, WR-300


SPECIFICATIONS

Pre-lacquered steel outside. Sanitary thermoformed plastic inside with embedded inner tray slides (polystyrene).
 45 mm, 40 kg/m³ injected polyurethane isolation.
 Forced draught cooling system with low vibration compressor.
 Inner evaporator with forced draught. Outer low maintenance condenser with forced draught.
 Digital display for electronic and digital control of temperature and defrosting.
 Double pane door with tinted glass and UV filter for sunlight protection.
 Black plastic covered steel grid removable shelves for easy cleaning.
 Equipment: 3 flat shelves and 1 tipped shelf for main bottles or the conservation of opened bottles (models WR-300/600) one flat unit for model WR-180.
 LED vertical lighting system.
 Working temperature: +5 °C, +16 °C (Room temperature: 32 °C).

Doors: 1
 Capacity: 400 L
 Bottle capacity: 72

DIMENSIONS

X Width	620 mm	X Gross width	690 mm
Y Depth	655 mm	Y Gross depth	650 mm
Z Height	1850 mm	Z Gross height	1965 mm
Net Weight	98,0 kg	Gross Weight	103,0 kg
Net volume	0,751 m ³	Gross volume	0,881 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,323 kW
Voltage	230V - 1N
Amperage	2,5A
Electric frequency	50/60Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-134a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,254 kW
Climate class	4
Cooling gas load	185,000 g

UNDERTAKEN TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	1+N
--------------------------	-----

